

ReinhardOil.DK ApS

Pro Lube



Pro Sil MOMENTIVE™

LIQUI MOLY GMBH · JERG-WIELAND-STR. 4 · D 7900 ULM

www.reinhardoil.dk \*Denmark

Telf. + 45 70 26 70 07

Fax. + 45 70 26 70 47



## LM 320 High-temperature Grease

A high-temperature grease for the long-term lubrication of greasing points which are exposed to extremely high operating temperatures, such as friction bearings, ball and roller bearings, special clutch and wheel-hub bearings.

LM 320 high-temperature grease is completely water-resistant and extraordinarily resistant to ageing, temperature and corrosion.

### Supplied in:

Tubes	100 g
Cans	1 kg
Drums	5 kg

### Technical Information

#### Description

High-temperature lubricating grease based on special temperature-resistant ingredients. Its composition guarantees effective long-term lubrication at normal and high temperatures.

#### Properties

Resistant to hot and cold water.  
Non-ageing and temperature-resistant.  
Reliable protection against rust and corrosion.  
Reduces friction and wear.  
Economical, thanks to high reliability.  
Can be used in centralized lubrication systems.  
Good anti-frictional properties.

#### Technical data

Type: inorganic thickeners  
Temperature range: - 25 °C to + 220 °C,  
for short periods  
up to + 250 °C  
NGLI consistency: no. 2  
Drop point  
to DIN 51 801: 270 °C  
Resistance to water: fully resistant

#### Applications

Long-term and "for life" lubrication at normal and high operating temperatures.  
For friction bearings, ball and roller bearings, special clutch and wheel-hub bearings.

#### Method of application

As for normal grease. Observe bearing manufacturers instructions. Clean bearings prior to initial filling. Do not mix with any other types of grease.

