Technical Data Sheet





Foodmax DWF Spray

Food grade dewatering and penetrating fluid

Description

Foodmax DWF Spray is a food grade multi-purpose penetrating lubricant containing with excellent water displacing properties.

Applications

Foodmax DWF spray is a non-toxic lubricating, penetrating and de-watering lubricant and is ideal for use on lightly loaded chains, bearings & slides in food and clean environments.

Benefits

• Temperature range -30 °C to 145 °C

Typical performance data

- Good anti wear properties
- Good dewatering properties
- Excellent penetration
- Excellent corrosion protection
- Does not contain mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- FDA listed ingredients under 21 CFR 178.3570
- Packed in a spray can for your convenience
- Also available in bulk packaging

	Test method	DWF
Appearance		Pale coloured liquid
Base oil type		Synthetic
Viscosity @ 40 °C, cSt		14
4-ball wear test, scar diameter, 40 kg/1 hr, mm	ASTM D2596	0,42
Copper corrosion test	ASTM D130	1b
Service temperatures, °C		-30 – 145

All performance data on this Technical Data Sheet are indicative only and can vary during production Matrix Specialty Lubricants BV - info@lubes-portal.com – www.lubes-portal.com