## reinhard oil





ReinhardOil.DK ApS - Helleruplund Allé 8 DK-2900 Hellerup - Denmark Telefon 70 26 70 07 - Telefax 70 26 70 47 smøremiddel specialisten

## Sunoco Sunamatic ATF DEXRON III G-34014

- <u>Description :</u> ATF designed to protect most passenger car, van and light truck automatic transmissions.
- Application : Wherever DEXRON III G, Dexron III F and other old Dexron III versions, DEXRON II-E, DEXRON II, DEXRON or Type A fluids are recommended.
- •

Wherever MERCON, M2C138-CJ or M2C166-H fluids are recommended In all automatic transmissions built by GM. Wherever Allison C-4 fluids are required. May be used in some hydraulic and compressor systems where excellent low temperature flow ability is required.

• Specifications :

Dexron III G-34014 Ford Mercon M940209 Allison C-4 20952194

Pro

Sil

MB 236.9 & Voith

• Advantages :

Additional savings that result from using just one fluid for most automatic transmission applications.

Oxidation resistance : product is formulated with excellent base stocks and special additives that minimize deterioration of the fluid through use.

Improved low temperature fluidity : excellent protection against wear during cold operating conditions and helps eliminate cold start stalling.

Transmission cleanliness : The additives prevent formation of deposits which affect the performance of delicate control valves.

Viscosity index : Excellent performance over a wide range of temperatures is possible through the use of high VI base oils along with a shear stable VI improver.

• Typical analysis :

density at 15 °C	0.865
viscosity at 40°C	33 cSt
viscosity at 100°C	7.5 cSt
viscosity at -40°C	15.500 cP
viscosity index	197
pour point	-48°C
flash point	190°C
Colour	red
Teknisk afdeling 2004-12-24 SQ	



